

XTOOL | F2

Quick Start Guide

Kurzanleitung | Guía de inicio rápido | Guide de démarrage rapide |
Guida rapida | Korte handleiding | Manual de referência rápida |
Skrócona instrukcja obsługi | クイックガイド | 빠른 시작 가이드 | 快速入门指南 |
快速使用指南

XTOOL





Multi-language versions and more information

To find user guides in multiple languages and more help, please visit support.xtool.com/article/2013 or scan the QR code.

Mehrsprachige Versionen und weitere Informationen

Falls Sie Benutzerhandbücher in mehreren Sprachen suchen und weitere Hilfe benötigen, besuchen Sie bitte support.xtool.com/article/2013 oder scannen Sie den QR-Code.

Versiones multilingües y más información

Para encontrar guías de usuario en varios idiomas y más ayuda, visite support.xtool.com/article/2013 o escanee el código QR.

Versions multilingues et informations complémentaires

Pour trouver des guides de l'utilisateur dans plusieurs langues et accéder à une assistance supplémentaire, veuillez consulter support.xtool.com/article/2013 ou scanner le code QR.

Versioni multilingue e ulteriori informazioni

Per manuali dell'utente in altre lingue o ulteriore assistenza, visitare support.xtool.com/article/2013 o scansionare il codice QR.

Meertalige versies en meer informatie

Ga voor gebruikershandleidingen in meerdere talen en meer hulp naar support.xtool.com/article/2013 of scan de QR-code.

Versões multi-idiomas e mais informações

Para encontrar manuais do utilizador em idiomas múltiplos e mais ajuda, visite, se faz o favor, support.xtool.com/article/2013 ou leia o código QR.

Wersje wielojęzyczne i więcej informacji

Aby znaleźć instrukcje obsługi w wielu językach i dodatkową pomoc, odwiedź stronę support.xtool.com/article/2013 lub zeskanuj kod QR.

複数言語バージョンと詳細情報

複数言語のユーザー ガイドと詳細なヘルプについては、support.xtool.com/article/2013にアクセスするか、QRコードをスキャンしてください。

다중 언어 버전 및 추가 정보

다중 언어로 된 사용 설명서와 추가 도움말을 찾으려면 support.xtool.com/article/2013 페이지를 방문하거나 QR 코드를 스캔하십시오.

多語言版本及更多資訊

如需取得其他語言版本的使用者指南或幫助資訊，請前往 support.xtool.com/article/2013 或掃描 QR code。

多语言版本及更多信息

如需获取其他语言版本的用户指南或更多帮助信息，请访问 support.xtool.com/article/2013 或扫描二维码。你也可以访问 s.makextool.com/wiki/f2 查看在线帮助。

support.xtool.com/article/2013



What's in the box

Meet your xTool F2

Get the machine ready

Use your xTool F2

More operations

Use accessories

Maintenance

01

02

04

07


09

10

13



* The English version is the original instructions verified by the manufacturer.

What's in the box



Meet your xTool F2

Product structure



Common machine states and indicator display



Logo indicator	Knob indicator	Machine state
Solid on	● Solid white	Not connected to the software
	● Solid yellow	Setting network
	● Solid blue	Connected to the software
	● Solid green	Processing completed
	● Solid purple	Firmware updating
	● Solid red	Exceptions occur
Blinking	● Blinking red for 3 times	Invalid operation
Going off	● Solid blue	Processing
	● Blinking white slowly	Enters sleep state if no operation is performed within 10 minutes


Specifications

Product name	xTool F2
Model	MKF-K005-002
Connection mode	Wi-Fi, USB, IP
Internal working area	115 mm × 115 mm
Maximum processing speed	6,000 mm/s


Size (W × D × H)	175 mm × 237 mm × 334 mm
Input power	25 V DC, 95 W
Working laser	12 W blue-light diode laser 5 W infrared laser
Working laser wavelength	Blue-light laser: 445 ± 15 nm Infrared laser: 1064 ± 5 nm
Maximum processing height	120 mm

Get the machine ready

1 Open the protective enclosure, and install the baseplate in the direction indicated by the arrow.




2 Pull down the field lens protector to remove it.



 Ensure that the protector is removed every time before you use the machine. If you won't use the machine for a long period of time, you can install the protector back to prevent the field lens from getting dusty.

3 Ensure that the emergency stop button is released. If it is pressed, rotate to release it.



Emergency stop button

If an emergency occurs, press the emergency stop button to shut off the machine.



After dealing with the emergency, rotate the emergency stop button to release it.

5 Install the pipe.



Pipe



If you need a desktop smoke purifier, purchase one and connect it to xTool F2 as instructed by the user manual.

4 Ensure the key is fully inserted.



You can use the key either as an access-control key or a remote interlock connector.

Access-control key

Removing the key can disable the machine's processing and related functions.


Remote interlock connector

For detailed instructions, scan the QR code or visit the link.




support.xtool.com/article/1367

6 Connect to a power supply.



Power adapter

Power cable




Use your xTool F2

Power on


Press the power button to turn on xTool F2.

 **Never use the emergency stop button as a power button.**

Use the emergency stop button only when an emergency occurs. Using it as a power button to turn on and off the machine may damage it.



(2) Use the USB cable to connect xTool F2 to your computer, and then connect xTool F2 in the software.



Operate xTool F2 with the software

(1) Visit s.xtool.com/software to download and install the software developed by xTool.



For details about how to use the software to operate xTool F2 to process materials, scan the QR code or visit the link.




support.xtool.com/product/60

More operations

Manual focus setting


Turn the knob to adjust the height of the laser module. When the red and blue light spots overlap, the focus is successfully set.



If turning the knob cannot overlap the red and blue spots, visit support.xtool.com/article/2373 or scan the QR code for reference, or you can contact customer support for help.





support.xtool.com/article/2373



Use accessories


Slatted panel

To cut a material, you are advised to use the slatted panel. It can reduce the areas burned and protect the baseplate during material processing.



L-shaped positioning piece


You can use the L-shaped positioning piece for batch processing. It helps you place materials in the same position for each processing task.




Touchscreen controller



Touchscreen controller (Not provided)




No touchscreen controller is included in the pack.




- **Up/Down button for laser module:** Lifts or lowers the laser module during manual focusing.
- **Framing button:** Press it once to start or stop framing.
- **Start/Stop button:** Press it once to start or stop material processing; press it twice consecutively to repeat the last processing task.



Before connecting the cable, ensure the power switch is in the OFF position.



Ensure that the side with the notch faces upward.



Rotary attachment




Rotary attachment (Not provided)



No rotary attachment is included in the pack.

There are three marking lines on the base of xTool F2. Depending on the working mode and level setting of your rotary attachment, align its front bottom edge to the corresponding marking line.



For details about how to use xTool F2 with the rotary attachment, scan the QR code or visit support.xtool.com/product/13 for reference.



support.xtool.com/product/13


⚠ Strictly follow the safety instructions to use xTool F2 with the rotary attachment. Set up a safety-controlled area under the guidance of the Laser Safety Officer (LSO), and take sufficient personal protective measures against laser risks.

Maintenance

 Disconnect power before maintaining the product.

Clean the field lens


When laser power attenuation occurs, for example, engraved patterns are shallow or materials can't be cut as expected, the field lens may get dirty. Clean it with the lint-free cloth moistened with alcohol.



Clean the fan module

When smoke runs out of the protective enclosure, the fan module may be blocked by dust. Clean it to ensure proper smoke exhausting.



(1) Remove the pipe.



(2) Open the cover, and then take out the fan module.



Screwdriver



Remove the connector

(3) Use a brush or other tools to clean both sides of the fan module.






Brush (Not provided)



The fan module can be rinsed with water, but do not soak it. Ensure it is completely dry before reinstalling.

(4) Install the fan module back to the main unit.



Lubricate the protective enclosure

If you can't move the protective enclosure up and down smoothly, apply grease to the edges of the two sides.

